

CONSTRUCTION IDEAS AT WORK

LOT#

PRODUCT DESCRIPTION

JS Crystal Clear Cure & Seal is a high solids transparent sealer formulated for interior and exterior concrete. JS Crystal Clear Cure & Seal is compatible with concrete surfaces cured and sealed with JS Cure & Seal 25. JS Crystal Clear Cure & Seal provides a high gloss wet look to concrete, exposed aggregate, decks, patios, and walls.

GENERAL USES

JS Crystal Clear Cure & Seal is used for curing, hardening, and dust proofing fresh concrete and sealing the surface of the concrete from stain and erosion that result from chemical attack.

STANDARDS

ASTM C 309
AASHTO M148
ASTM C1315, Class A

INSTRUCTIONS FOR USE

Surface Preparation

New concrete: JS Crystal Clear Cure & Seal should be applied to green concrete as soon as the water sheen has disappeared from the surface and the concrete can be walked upon. For vertical sur-

faces, JS Crystal Clear Cure & Seal should be applied as soon as the forms have been stripped and the surface has been rubbed.

Old concrete: JS Crystal Clear Cure & Seal should be applied only after all stains have been removed.

Application

JS Crystal Clear Cure & Seal may be applied to the surface by spray, brush, or short-nap mohair roller.

Coverage

One gallon will cover from 200-600 sq. ft./gal., depending upon the surface texture and specification requirements. For application to vertical surfaces, JS Crystal Clear Cure & Seal should be applied at the rate of 600 sq. ft./gal. Where a 200 sq. ft./gal. is desired, JS Crystal Clear Cure & Seal should be applied in multiple thin applications at a rate of 600 sq. ft./gal. per application to insure uniformity of application and avoid sagging and running of the material.

STORAGE AND HANDLING

Shelf Life

When stored in a controlled environment in accordance to Jobsite Supply recommendations and left in its original unopened container, JS Crystal Clear Cure

& Seal will maintain its designed performance characteristics for 12 months from date of manufacture.

LIMITATIONS/WARNING

- Refer to Material Safety Data Sheet prior to use.
- JS Crystal Clear Cure & Seal should be applied in a well-ventilated room; it should not be applied if proper venting is not available.
- Before using JS Crystal Clear Cure & Seal, personnel should read handling instructions included on all labels.
- Rubber wheeled tires may leave marks.
- Do not over apply.

TECHNICAL SERVICES

Jobsite Supply Technical Service Department provides complete product and technical support.

PACKAGING

- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

KEEP PRODUCT OUT OF REACH OF CHILDREN



HIMS
Hazard Ratings

- 0 - Least
- 1 - Slight
- 2 - Moderate
- 3 - High
- 4 - Extreme



DANGER

Keep away from heat, sparks & flames. Do not cut, puncture or weld on or near empty or full containers. Do not re-use container for any purpose, until commercial clean