

# JS Form Release

## Neutral Form Release Agent

CONSTRUCTION IDEAS AT WORK

LOT#

### PRODUCT DESCRIPTION

JS Form Release is a premium grade, chemically neutral, petroleum based form release agent. JS Form Release is non-reactive with the alkali in the concrete and creates a barrier that inhibits the bonding of fresh concrete to the formwork. Forms are ready for re-use almost instantly. JS Form Release produces a smooth, void free, architectural concrete surface. VOC compliant.

### GENERAL USES

JS Form Release will aid in the release of the form from hardened concrete on the widest range of forming material.

### STANDARDS

Meets the requirements of Corps of Engineers specifications CW 03101, section 2.1.2.

### INSTRUCTIONS FOR USE

JS Form Release should be applied in a thin uniform film with a sprayer, brush, or roller. No special application equipment is necessary, but a spray application is the most practical. Pounding or puddling is to be avoided.

### Specific applications are as follows:

*Aluminum, High Density Plywood, Plastic or Steel*  
1750 sq. ft./U.S. gallon

*Medium Density Plywood*  
1500 sq. ft./U.S. gallon

*BB Grade Plyform*  
1000 sq. ft./U.S. gallon

*Plywood & Other Dimensional Lumber*  
750 sq. ft./U.S. gallon

### LIMITATIONS/WARNING

- Refer to Material Safety Data Sheet before use.
- Do not over apply.
- Do not use as a bondbreaker for tilt-up construction.
- Do not use on styrofoam or latex molds.
- Do not use on plaster molds unless coated with a suitable sealer.
- Colder temperatures will increase the viscosity of JS Form Release.

**Combustible...** Contains petroleum distillates. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame.

### TECHNICAL SERVICES

Jobsite Supply Technical Service Department provides complete product and technical support.

### PACKAGING

- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

**KEEP PRODUCT OUT OF REACH OF CHILDREN**



HIMS  
Hazard Ratings

- 0 - Least
- 1 - Slight
- 2 - Moderate
- 3 - High
- 4 - Extreme



**DANGER**  
Keep away from heat, sparks & flames. Do not cut, puncture or weld on or near empty or full containers. Do not re-use container for any purpose, until commercial clean