

JS Honey Brown Brown Pigmented Acrylic Sealer

CONSTRUCTION IDEAS AT WORK

LOT#

PRODUCT DESCRIPTION

JS Honey Brown is a premium, high solid, UV stable, single component, lightly brown pigmented, 100% acrylic sealer designed to provide a high gloss protective finish. JS Honey Brown will cure and seal exposed architectural concrete as well as hide finishing flaws and color variations.

GENERAL USES

JS Honey Brown is used for curing and sealing concrete surfaces. JS Honey Brown is applied as a protective seal coat on the concrete surfaces. The sealer provides protection to the concrete surface against abrasion and spillage while providing a rich brown color luster to the concrete surface.

STANDARDS

ASTM C309
AASHTO M148

INSTRUCTIONS FOR USE

Surface Preparation

New concrete: JS Honey Brown should be applied to green concrete as soon as the water sheen has disappeared from the surface and the concrete can be walked upon. For vertical surfaces, JS Honey Brown should be applied as soon as the forms

have been stripped and the surface has been rubbed.

Old concrete: JS Honey Brown should be applied after all stains have been removed.

Application

JS Honey Brown may be applied to the surface by spray, brush, or short-nap mohair roller. Mix prior to use.

Coverage

One gallon will cover from 200-600 sq. ft., depending upon the surface texture and specification requirements.

Horizontal Surfaces

It is suggested JS Honey Brown be applied in two applications. When a coverage of 200 sq.ft./gal is desired, two coats applied at 400 sq.ft./gal is recommended.

Vertical Surfaces

To avoid running and sagging of the material, it is suggested that JS Honey Brown be applied at 600 sq.ft./gal. To obtain a finished coverage of 200 sq.ft./gal, apply multiple thin applications at 600 sq.ft./gal will be required.

STORAGE AND HANDLING

Shelf Life: When stored in a controlled environment in accordance to Jobsite Supply recommendations and left in its original unopened container, JS Honey Brown will

maintain its designed performance characteristics for 12 months from date of manufacture.

LIMITATIONS/WARNING

- Refer to material safety data sheet prior to use.
- JS Honey Brown should be applied in a well-ventilated room; it should not be applied if proper venting is not available.
- Because JS Honey Brown has a low flash point, smoking must not be permitted.
- The material should not be exposed to heat or flame of any kind.
- Rubber wheeled tires may leave marks.
- Do not over apply.

TECHNICAL SERVICES

Jobsite Supply Technical Service Department provides complete product and technical support.

PACKAGING

- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

KEEP PRODUCT OUT OF REACH OF CHILDREN



HIMS
Hazard Ratings

- 0 - Least
- 1 - Slight
- 2 - Moderate
- 3 - High
- 4 - Extreme



DANGER

Keep away from heat, sparks & flames. Do not cut, puncture or weld on or near empty or full containers. Do not re-use container for any purpose, until commercial clean