

## Product Description

JS Super 2 is a premium, chemically reactive, petroleum based form release agent. JS Super 2 Form Release reacts with the alkali in the concrete to form a soap film that inhibits the bonding of fresh concrete to the formwork. Forms are ready for re-use almost instantly. JS Super 2 Form Release produces a smooth, void free, architectural concrete surface. VOC compliant.

## General Uses

JS Super 2 Form Release will aid in the release of the form from hardened concrete on the widest range of forming materials.

## Features

- Ensures easy stripping of forms.
- Produces smooth natural architectural surfaces – chemical action is not harmful to the concrete surface.
- Will not retard, etch, or soften concrete surfaces, even if over-applied.
- Run-down is reduced and reinforcing steel stays cleaner.
- May be used on concrete structures that will store portable water.
- Has a positive release that keeps forms clean – no cleaning between pours is necessary.
- Repeated use makes wood forms water-repellent and extends their useful life.
- Inhibits rust formation on steel forms.
- Easy to apply.
- No deleterious effect upon the natural bonding characteristics of secondary toppings or coatings, caulks, or sealants.
- Reduces bug holes and extends the life of most forming materials.

## Standards

This product meets the requirements of Corps of Engineers specifications CW 03101, section 2.1.2.

## Instructions For Use

JS Super 2 Form Release should be applied in a thin uniform film with a sprayer, brush, or roller. No special application

equipment is necessary, but a spray application is the most practical. Pounding or puddling is to be avoided.

## Specific applications are as follows:

### *Aluminum, High Density Plywood, Plastic or Steel*

2500 sq. ft. / U.S. gallon

### *Medium Density Plywood*

2000 sq. ft. / U.S. gallon

### *BB Grade Plyform*

1500 sq. ft. / U.S. gallon

### *Plywood & Other Dimensional Lumber*

1200 sq. ft. / U.S. gallon

## Limitations/Warning

- Refer to Safety Data Sheet before use.
- Do not over apply.
- Do not use as a bondbreaker for tilt-up construction.
- Do not use on styrofoam or latex molds.
- Do not use on plaster molds unless coated with a suitable sealer.
- Colder temperatures will increase the viscosity of JS Super 2 Form Release.

Combustible... Contains petroleum distillates. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame.

## Packaging

- 275 gal (1054 L) totes
- 55 gallon (208 L) drums
- 5 gallon (18.9 L) pails

## Technical Services

Jobsite Supply Technical Service Department provides complete product and technical support.

**Limited Warranty:** Subject to the conditions and limitations stated below, manufacturer warrants this product to be free from manufacturing defects for a period of one (1) year from the date of purchase of the product, as conditions of this limited warranty, you may be required to provide proof of product purchase and use. **DISCLAIMER:** THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. **EXCLUSIVE REMEDY:** The sale and exclusive remedy for a breach of this limited warranty is replacement of the product that is proven defective. In the event this sole and exclusive remedy fails of its essential purpose, the liability of manufacturer is limited to return of the original purchase price. **EXCLUSION:** Manufacturer is not responsible for workmanship not in accordance with instructions and industry standard guidelines. MANUFACTURER IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.