

JS UNIPRIMER

A ready-to-use prime adhesive designed for use with JS Uniflow self leveling underlayment.

PRODUCT DESCRIPTION

A ready to use prime adhesive designed for use with Universal Uniflow self leveling underlayment. A milky-colored re-emulsifiable primer.

GENERAL USES

- Seals the substrate and improves bonding.
- Use for all interior installations of Universal's Uniflow self leveling underlayment.

INSTRUCTIONS FOR USE

Surface Preparation:

All substrates must be structurally sound, stable, solid, clean and free of dust, oil, grease, paint, tar, wax, sealers, curing compounds, form release agents, primers laitance, loose particles and foreign substances and debris which could reduce or impair adhesion.

Mechanically roughen surface, especially in the case of dense and smooth concrete, by sandblasting, water-jetting, shot blasting, scarifying or grinding as required.

Mixing:

Agitate to assure that all solids are homogenous.

Application:

Apply with a push broom or thick nap paint roller.

Remove any puddles and allow to dry to a clear, thin film (2 hours minimum, 24 hours maximum).

Apply underlayments or repair materials as soon as the UniPrimer is dry to the touch.

Install underlayments when the JS UniPrimer has dried to a transparent film, no longer milky in color.

Concrete may require two applications of primer. Re-apply UniPrimer after first application dries within 30 minutes at 70°F (21°C).

Coverage: 150-250 sq. ft. / gal.

Cleaning:

Water cleanup prior to cure.

PACKAGING

- 1 gallon jugs (3.8 l)
- 5 gallon pails (18.9 l)
- 55 gallon drums (208 l)

LIMITATIONS/WARNING

- Refer to material safety data sheet prior to use.
- Always check primer adhesion prior to placing self leveling underlayment.
- Protect from freezing. Do not use below 40°F.
- Do not take internally.
- Harmful if ingested.
- Keep product out of reach of children.

TECHNICAL SERVICES

Universal Form - Chemical Division Technical Service Department provides complete product and technical support.